

**SCHOTTKY BARRIER RECTIFIER**

**VOLTAGE RANGE 20 to 200 Volts CURRENT 10.0 Ampere**

**FEATURES**


- \* High reliability
- \* Low switching loss
- \* Low forward voltage drop
- \* High current capability
- \* High switching capability

**MECHANICAL DATA**

- \* Epoxy: Device has UL flammability classification 94V-0
- \* Case: Molded plastic
- \* Lead: MIL-STD-202E method 208C guaranteed
- \* Mounting: position: Any
- \* Weight: 0.33 grams

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



**MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)**


RATINGS	SYMBOL	SR1020K	SR1030K	SR1035K	SR1040K	SR1045K	SR1050K	SR1060K	SR1080K	SR10100K	SR10150K	SR10200K	UNITS	
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	20	30	35	40	45	50	60	80	100	150	200	Volts	
Maximum RMS Voltage	V <sub>RMS</sub>	14	21	25	28	32	35	42	56	70	105	140	Volts	
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	30	35	40	45	50	60	80	100	150	200	Volts	
Maximum Average Forward Rectified Current at Derating Case Temperature	I <sub>O</sub>	10.0											Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I <sub>FSM</sub>	150											Amps	
Typical Thermal Resistance (Note 1)	R <sub>θJC</sub>	2.0											°C/W	
	R <sub>θJA</sub>	60												
Typical Junction Capacitance (Note 2)	C <sub>J</sub>	700					450							pF
Operating Temperature Range	T <sub>J</sub>	150											°C	
Storage Temperature Range	T <sub>STG</sub>	-55 to + 150											°C	

**ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)**


CHARACTERISTICS	SYMBOL	SR1020K	SR1030K	SR1035K	SR1040K	SR1045K	SR1050K	SR1060K	SR1080K	SR10100K	SR10150K	SR10200K	UNITS	
Maximum Instantaneous Forward Voltage at 10.0A DC	V <sub>F</sub>	.65					.75			.85				Volts
Maximum Average Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	@T <sub>A</sub> = 25°C											mA	
		@T <sub>A</sub> = 100°C											2	mA

- NOTES :
1. Thermal Resistance : Heat-sink case mounted or if PCB mounted.
  2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.□
  3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".
  4. Suffix "R" for Reverse Polarity.
  5. Suffix "S" for D2-PAK Pkg.


# RATING AND CHARACTERISTICS CURVES ( SR1020K THRU SR10200K )




**FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE**




**FIG.2 TYPICAL REVERSE CHARACTERISTICS**



**FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**



**FIG.4 TYPICAL JUNCTION CAPACITANCE**



**FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**

## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.