

VARISTOR SILICON RECTIFIER

CURRENT 0.5 Ampere

FEATURES


- * Low cost
- * Low leakage
- * Low forward voltage drop
- * High current capability

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: Device has UL flammability classification 94V-0
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.33 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	VR60-D-S-R01	UNITS
Maximum Average Forward Rectified Current at TA = 75 °C	Io	0.5	Amps
Operating Temperature	TJ	150	°C
Storage Temperature Range	TSTG	-55 to + 150	°C

ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)

CHARACTERISTICS	SYMBOL	VR60-D-S-R01	UNITS
Maximum Leak Current at 0.2V Forward Voltage	IF	20	uAmps
Maximum Forward voltage Drop per element at 1.0A DC	VF	1.5	Volts
Maximum Forward voltage Drop per element at 1.0mA DC		0.5	

RATING AND CHARACTERISTICS CURVES (VR60-D-S-R01)




FIG.1 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT





FIG.2 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



Double orange cathode band

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.